

CORROSION RESISTANT SHEET PRODUCTS

Construction Sales



United States Steel

United States Steel is dedicated to becoming the best steel supplier to the construction industry. We offer a complete line of coated sheet products including bare and pre-painted galvanized and Galvalume® as well as acrylic coated galvanized and Galvalume® sheet branded as Acryzinc® and Acrylume®.

Our value-added flat-rolled products are produced on world-class coating lines across the United States. These products are manufactured to meet customer specifications with respect to corrosion resistance, strength level and/or formability requirements of the steel's thickness, width, surface quality and surface finish. Our experienced quality and application engineering teams work closely with our customers to develop steel solutions for today and the future.

With the addition of verdeX™ sustainable steel solutions, we are advancing the next generation of stronger and lighter weight steels with a lower carbon footprint. Whatever the challenge, our mission is to design the solution to meet the ever-changing needs of our construction customers.



Contact Us:

constructionsales@uss.com | 1-877-798-7909

Follow our social media:



Fairfield Works

Hot Dipped Galvanized / Acryzinc®

ASTM A653 CS Type B, SS

Grades 33, 37, 40, 50, 55, 57, 70, 80

Acryzinc® CS Type B, SS Grades 33, 37, 40, 50, 80

Gauges: 0.0133-0.040, **Width:** 24-29"

Galvalume® / Acrylume®

ASTM A792 CS Type B, FS Type B, SS

Grades 33, 37, 40, 50, 80

Gauges: 0.0135-0.04, **Width:** 24-49"

Double G Coatings, LP

ASTM A792 CS Type B, FS Type B, SS

Grades 33, 37, 40, 50, 55, 57, 70, 80

Gauges: 0.013-0.036, **Width:** 24-49"

Gary Works

Midwest Plant

Hot Dipped Galvanized

ASTM A653 CS Type B, FS Type B, DDS, EDDS, SS

Grades 33, 37, 40, 50, 57, 70, 80

Gauges: 0.012-0.036, **Width:** 26-50"

Hot Dipped Galvanized

ASTM A653 CS Type B, FS Type B, DS Type B, DDS, SS

Grades 33, 40, 50, 55

Gauges: 0.023-0.114, **Width:** 35.5-72"

Granite City Works

Hot Dipped Galvanized

ASTM A653 CS, FS, SS Grades 33, 37, 40, 50, 55, 57, 80

Gauges: 0.013-0.0365, **Width:** 24-49"

Galvalume®

ASTM A792 CS Type B, FS Type B, SS

Grades 33, 37, 40, 50, 80

Gauges: 0.014-0.0365, **Width:** 24-49

Great Lakes Works

Hot Dipped Galvanized

ASTM A653 CS Type B, FS Type B, SS, BH, DDS, EDDS

Grades 33, 40, 50, 70, 80

Gauges: 0.017-0.080, **Width:** 32-73"

All figures in inches.

All thickness, widths, and grades not listed; please inquire

Mon Valley Works

Irvin Plant

Hot Dipped Galvanized

ASTM A653 CS Type B/ DS Type B, DDS, EDDS, SS

Specified Hardness

Gauges: 0.036-0.1601, **Width:** 24-52"

Hot Dipped Galvanized

ASTM A653 CS Type B/ DS Type B, DDS, EDDS, SS Specific Hardness

Gauges: 0.015- 0.05, **Width:** 24-48"

Fairless Plant

Hot Dipped Galvanized

ASTM A653 CS Type B, FS Type B, DDS, EDDS, SS

Grades 33, 37, 40, 50, 55, 80

Gauges: 0.017-0.08, **Width:** 24-63"

PRO-TEC Coating Company

Hot Dipped Galvanized

ASTM A653 CS Type B, HSFS, Bake Hard (BH), DDS, EDDS

SS Grade 33, 37, 40, 50, 80

Gauges: 0.023-0.103, **Width:** 36-72"

Big River Steel

Hot Dipped Galvanized

ASTM A653 CS Type B, FS Type B, DDS, EDDS, SS Grades

33, 37, 40, 50, 55, 60, 70, 80

Gauges: 0.0140-0.106", **Width:** 35-72"

Coming Summer 2024

Hot Dipped Galvanized

ASTM A653, CS Type B, FS Type B, DDS, EDDS, SS

Grades 33, 37, 40, 50, 55, 60, 70, 80

Gauges: 0.0120 - 0.059, **Width:** 35-61"

Galvalume®/Acrylume®

ASTM A792 CS Type B, FS Type B, SS

Grades 33, 37, 40, 50, 80

Gauges: 0.0120 - 0.059, **Width:** 35-61"

New Coil Coating Paint Line

This line will offer ~190,000 tons per year production capacity.

Coating Weight Options

Hot Dipped Galvanized

G30 – G235

Galvalume®

AZ30 LCM – AZ60

We are proud members of the following metal construction industry groups:



PLEASE NOTE: All price quotations, request for quotations, proposals, offers and resulting contracts in whatever form (including those resulting from purchase orders, order confirmations, production/shipping releases or otherwise) relative to U.S. Steel products shall be subject exclusively to the USS Standard Terms and Conditions of Sale found at: www.ussteel.com/sites/default/files/USS-Standard-Terms-and-Conditions-of-Sale.pdf. Buyer's placement of an order or releases for, or taking delivery of, any U. S. Steel product which is the subject of any such document constitutes your acceptance of same. If you need assistance accessing the USS Standards Terms and Conditions of Sale, please contact your U. S. Steel Account Representative or Account Manager for assistance. Galvalume® is a registered trademark of BIEC International Inc. Used under license.