



United States Steel Corporation

Galvanizing Dross Safety Data Sheet (SDS)

USS IHS Number: 1824

Locations: Fairless, Fairfield, Gary, Granite City, Great Lakes, Hamilton, Irvin, and Midwest

Original: 12/16/2010

Revision: 12/31/2020

Section 1 – Identification

1(a) Product Identifier used on Label: Galvanizing Dross

1(b) Other Means of Identification: Zinc Dross

1(c) Recommended use of the chemical and restrictions on use: None

1(d) Name, Address, and Telephone Number:

United States Steel Corporation Phone number: (412) 433-6840 (8:00 am to 5:00 pm)
600 Grant Street, Room 1662 FAX: (412) 433-5019
Pittsburgh, PA 15219-2800

1(e) Emergency Phone Number: 1-800-262-8200 (CHEMTREC)

Section 2 – Hazard(s) Identification

2(a) Classification of the Chemical: Galvanizing Dross is considered a hazardous material according to the criteria specified in REACH [REGULATION (EC) No 1907/2006] and CLP [REGULATION (EC) No 1272/2008] and OSHA 29 CFR 1910.1200 Hazard Communication Standard. The categories of Health Hazards as defined in "GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3" United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal Word, Hazard Statement(s), Symbols and Precautionary Statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)
	Single Target Organ Toxicity (STOT) Repeat Exposure - 2	WARNING	May cause damage to lungs through prolonged or repeated exposure.

Precautionary Statement(s):

Prevention	Response	Storage/Disposal
Do not breathe dusts/ fumes.	Get medical advice/attention if you feel unwell.	Dispose of contents in accordance with federal, state and local regulations.

2(c) Hazards not Otherwise Classified: None Known

2(d) Unknown Acute Toxicity Statement (Mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical Name, Common Name (Synonyms), CAS Number and Other Identifiers, and Concentration:

Chemical Name	CAS Number	EC Number	% weight
Zinc	7440-66-6	231-175-3	88 - 99.9
Iron	7439-89-6	231-096-4	0.1 - 6
Aluminum	7429-90-5	231-072-3	0-3
Silicon	7440-21-3	231-130-8	0-3

EC- European Community

CAS- Chemical Abstract Service

Section 4 – First-aid Measures

4(a) Description of Necessary Measures:

- **Inhalation:** Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

Galvanizing Dross

USS IHS No.: 1824

Rev. 12/20

Section 4 – First-aid Measures (continued)

4(a) Description of Necessary Measures (continued):

- **Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention if you feel unwell.
- **Skin Contact:** If skin irritation occurs: Get medical advice/attention.
- **Ingestion:** Get medical advice/attention if you feel unwell.

4(b) Most Important Symptoms/Effects, Acute and Delayed (Chronic):

Acute effects:

- **Inhalation:** Excessive exposure to high concentrations of dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract.
- **Eye:** Excessive exposure to high concentrations of dust may cause irritation to the eyes. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- **Skin:** Skin contact with dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- **Ingestion:** Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of dust may cause nausea or vomiting.

Chronic Effects:

Long-term inhalation exposure to high concentrations (over-exposure) of agents that produce lung disorders may act synergistically with inhalation of oxides, vapors or dusts of this product to cause toxic effects.

4(c) Immediate Medical Attention and Special Treatment: Treat symptomatically.

Section 5 – Fire-fighting Measures

5(a) Suitable (and Unsuitable) Extinguishing Media: Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards Arising from the Chemical: Not applicable for solid product.

5(c) Special Protective Equipment and Precautions for Fire-fighters: Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: Not applicable in solid state. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust. Fine, dry material should be removed by vacuuming or wet sweeping methods to prevent spreading of dust. Avoid using compressed air. Do not release into sewers or waterways. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations.

6(b) Methods and Materials for Containment and Clean Up: Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

Section 7 - Handling and Storage

7(a) Precautions for Safe Handling: Operations with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Practice good housekeeping. Avoid breathing metal fumes and/or dust.

7(b) Conditions for Safe Storage, including any Incompatibilities: Avoid storage with strong acids

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): The following exposure limits are offered as reference, for an experience industrial hygienist to review.

Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴
Zinc	15 mg/m ³ (as zinc oxide, total dust) 5.0 mg/m ³ (as zinc oxide, respirable fraction & zinc oxide fume)	2.0 mg/m ³ (as zinc oxide, respirable fraction ⁵) “STEL” 10 mg/m ³ (as zinc oxide, respirable fraction)	5.0 mg/m ³ (as zinc oxide dust or fume) “STEL” 10 mg/m ³ (as zinc oxide fume) “C” 15 mg/m ³ (as zinc oxide dust)	500 mg/m ³ (as zinc oxide)
Iron	10 mg/m ³ (iron oxide fume)	5.0 mg/m ³ (iron oxide, respirable fraction)	5.0 mg/m ³ (iron oxide dust and fume)	2,500 mg/m ³ (as Fe)
Silicon	15 mg/m ³ (total dust) 5.0 mg/m ³ (as respirable fraction)	NE	10 mg/m ³ (as total dust) 5.0 mg/m ³ (as respirable dust)	NE

Section 8 - Exposure Controls / Personal Protection (continued)

8(a) Occupational Exposure Limits (OELs) (continued):

Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴
Aluminum	15 mg/m ³ (as aluminum oxide, metal & insoluble compounds, total dust) 5.0 mg/m ³ (as aluminum oxide, metal & insoluble compounds, respirable fraction)	1.0 mg/m ³ (as metal & insoluble compounds, respirable fraction)	10 mg/m ³ (as metal & insoluble compounds, total dust) 5.0 mg/m ³ (as metal & insoluble compounds, respirable fraction)	NE

NE - None Established

1. OSHA PELs (Permissible Exposure Limits) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A ("C") designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes. DSEN – May cause dermal sensitization. This notation is used to indicate the potential for dermal sensitization resulting from the interaction of an absorbed agent and ultraviolet light (i.e. photosensitization). RSEN – May cause respiratory sensitization.
3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL)- Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994. Ca is designated as carcinogen.
5. Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH 2020 TLVs[®] and BEIs[®] Appendix D, paragraph C.

8(b) Appropriate Engineering Controls: Local exhaust ventilation should be used to control the emission of air contaminants. General dilution ventilation may assist with the reduction of air contaminant concentrations. Emergency eye wash stations and deluge safety showers should be available in the work area.

8(c) Individual Protection Measures:

- **Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure and powered-air do not protect workers in oxygen-deficient atmospheres.

- **Eyes:** Wear appropriate eye protection to prevent eye contact. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely.
- **Skin:** Wear appropriate personal protective clothing to prevent skin contact. For operations, which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for burning or handling operations.
- **Other protective equipment:** An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties

9(a) Appearance (physical state, color, etc.): Fused agglomerate mass or dust; silver-gray metallic	9(j) Upper/Lower Flammability or Explosive Limits: NA
9(b) Odor: NA	9(k) Vapor Pressure: NA
9(c) Odor Threshold: NA	9(l) Vapor Density (Air = 1): Approx. 7.1 SG
9(d) pH: ND	9(m) Relative Density: NA
9(e) Melting Point/Freezing Point: 787°F (zinc), 419°C	9(n) Solubility(ies): NA
9(f) Initial Boiling Point and Boiling Range: ND	9(o) Partition Coefficient n-octanol/water: NA
9(g) Flash Point: NA	9(p) Auto-ignition Temperature: ND
9(h) Evaporation Rate: NA	9(q) Decomposition Temperature: ND
9(i) Flammability (solid, gas): Non-flammable, non-combustible	9(r) Viscosity: ND

NA - Not Applicable

ND - Not Determined for product as a whole

Galvanizing Dross

USS IHS No.: 1824


Rev. 12/20

Section 10 - Stability and Reactivity

- 10(a) Reactivity:** Not Determined (ND)
- 10(b) Chemical Stability:** Galvanizing Dross is stable under normal storage and handling conditions.
- 10(c) Possibility of Hazardous Reaction:** None Known
- 10(d) Conditions to Avoid:** Storage with strong acids or calcium hypochlorite.
- 10(e) Incompatible Materials:** Will react with strong acids to form hydrogen.
- 10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition can produce fumes containing oxides of iron as well as other elements.

Section 11 - Toxicological Information

11(a-e) Information on Toxicological Effects: The following toxicity data has been determined for Galvanizing Dross by using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

Hazard Classification	Hazard Category		Hazard Symbols	Signal Word	Hazard Statement
	EU	OSHA			
STOT Following Repeated Exposure (covers Categories 1 and 2)	NR	2 ^j		Warning	May cause damage to lungs through prolonged or repeated exposure.

* NR Not Rated - Available data does not meet criteria for classification.

The Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

- a. No LC₅₀ or LD₅₀ has been established for Galvanizing Dross. The following data has been determined for the components:
 - **Zinc:** Rat LD₅₀ > 2000 mg/kg
 - **Iron:** Rat LD₅₀ = 1060 mg/kg (IUCLID) (Oral)
 - **Aluminum:** Rat LD₅₀ > 15.9 g/kg (REACH)
 - **Silicon:** LD₅₀ = 3160 mg/kg (Oral/Rat)
- b. No Skin (Dermal) Irritation data available for Galvanizing Dross as a mixture or its individual components.
- c. No Eye Irritation data available for Galvanizing Dross as a mixture. The following Eye Irritation information was found for the components:
 - **Iron:** Irritating when administered as Iron metal. Rabbit Draize - irritating (IUCLID).
- d. No Skin (Dermal)/Respiratory Sensitization data available for Galvanizing Dross as a mixture or its individual components.
- e. No Aspiration Hazard data available for Galvanizing Dross as a mixture or its individual components.
- f. No Germ Cell Mutagenicity data available for Galvanizing Dross as a mixture. The following Germ Cell Mutagenicity information was found for the components:
 - **Iron:** IUCLID has found some positive and negative findings *in vitro*.
 - **Aluminum:** IUCLID; ATSDR have found this ingredient is not mutagenic *in vitro*; but has marginal effects *in vivo*.
- g. Carcinogenicity: IARC, NTP, and OSHA do not list Galvanizing Dross or its individual components as carcinogens. The following Carcinogenicity information was found for the components:
 - **Aluminum (metal and insoluble compounds):** IARC-1 (production), carcinogen to humans; ACGIH TLV-A4, not classifiable as a human carcinogen
 - **Zinc (compounds, oxide, as Zn):** EPA-II, inadequate information to assess carcinogenic potential & EPA-D not classifiable as to human carcinogenicity & EPA-I, data are inadequate for assessment of human carcinogenic potential
 - **Iron Oxide (Fe₂O₃):** IARC-3, unclassifiable as to carcinogenicity in humans; ACGIH TLV-A4, not classifiable as a human carcinogen
- h. No Toxic Reproduction data available for Galvanizing Dross as a mixture or its individual components.
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for Galvanizing Dross as a mixture. The following STOT following a Single Exposure data was found for the components:
 - **Iron:** Irritating to Respiratory tract.
 - **Aluminum:** Repeated exposure associated with Asthma, fibrosis in lungs and encephalopathy in humans.
- j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for Galvanizing Dross as a whole. The following STOT following Repeated Exposure data was found for the components:
 - **Aluminum:** Reviews have found chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2020, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s):

Acute Effects by Component:

- **ZINC:** Not Reported/ Not Classified
- **IRON:** Iron is harmful if swallowed, causes skin irritation, and causes eye irritation.

Section 11 - Toxicological Information (continued)

Acute Effects by Component (continued):

- **ALUMINUM:** Not Reported/ Not Classified
- **SILICON and OXIDES:** May be harmful if swallowed.

Delayed (chronic) Effects by Component:

- **ZINC:** Zinc Residue CGLs are a low health risk by inhalation and should be treated as a nuisance dust. Inhalation of zinc oxide fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.
- **IRON:** Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign lung disease, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.
- **ALUMINUM:** Chronic inhalation of finely divided powder has been reported to cause pulmonary fibrosis and emphysema. Repeated skin contact has been associated with bleeding into the tissue, delayed hypersensitivity and granulomas. Chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.
- **SILICON and OXIDES:** Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No data available for the product, **Galvanizing Dross** as a whole. However, individual components of the product have been found to be toxic to the environment. Dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- **Zinc:** EU RAR lists as Category 1 Very toxic to aquatic life with long lasting effects.

12(b) Persistence & Degradability: No Data Available

12(c) Bioaccumulative Potential: No Data Available

12(d) Mobility (in soil): No Data Available

12(e) Other Adverse Effects: None Known

Additional Information:

Hazard Category: Category 1

Signal Word: Warning

Hazard Symbol:



Hazard Statement: Very Toxic to aquatic life with long lasting effects.

Section 13 - Disposal Considerations

Disposal: **Galvanizing Dross** should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

Container Cleaning and Disposal: Follow applicable federal, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC):10-05-10 (dross and skimmings that are flammable or emit, upon contact with water, flammable gases in dangerous quantities), 10-05-11 (dross and skimmings other than those mentioned in 10-05-10) or 10-03 (dangerous waste).

Please note this information is for **Galvanizing Dross** in its original form. Any alterations can void this information.

Section 14 - Transport Information

14 (a-g) Transportation Information:

US Department of Transportation (DOT) under 49 CFR 172.101 does not regulate **Galvanizing Dross** as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: NOT DOT Regulated Shipping Symbols: NA Hazard Class: NA UN No.: NA Packing Group: NA DOT/IMO Label: NA Special Provisions (172.102): NA	Packaging Authorizations a) Exceptions: NA b) Non-bulk: NA c) Bulk: NA	Quantity Limitations a) Passenger Aircraft or Rail: NA b) Cargo Aircraft Only: NA Vessel Stowage Location: NA DOT reportable quantities: NA
---	---	--

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Galvanizing Dross

USS IHS No.: 1824

Rev. 12/20

Section 14 - Transport Information (continued)

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate **Galvanizing Dross** as a hazardous material.

Shipping Name: NOT DOT Regulated Classification Code: NA UN No.: NA Packing Group: NA ADR Label: NA Special Provisions: NA Limited Quantities: NA	Packaging a) Packing Instructions: NA b) Special Packing Provisions: NA c) Mixed Packing Provisions: NA	Portable Tanks & Bulk Containers a) Instructions: NA b) Special Provisions: NA
--	--	---

International Air Transport Association (IATA) does not regulate **Galvanizing Dross** as a hazardous material.

Shipping Name: NOT DOT Regulated Class/Division: NA Hazard Label (s): NA UN No.: NA Packing Group: NA Excepted Quantities (EQ): NA	Passenger & Cargo Aircraft		Cargo Aircraft Only Pkg Inst: NA Max Net Qty/Pkg: NA	Special Provisions: NA ERG Code: NA
	Limited Quantity (EQ)			
	Pkg Inst: NA	Pkg Inst: NA		
	Max Net Qty/Pkg: NA	Max Net Qty/Pkg: NA		

Pkg Inst – Packing Instructions

Max Net Qty/Pkg – Maximum Net Quantity per Package

ERG – Emergency Response Drill Code

Galvanizing Dross does not have a **Transport Dangerous Goods (TDG)** classification.

Section 15 - Regulatory Information

Regulatory Information: *The following listing of regulations relating to a U. S. Steel product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.*

This product and/or its constituents are subject to the following regulations:

SARA Potential Hazard Categories: Immediate Acute Health Hazard, Delayed Chronic Health Hazard

Section 313 Supplier Notification: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

CAS #	Chemical Name	Percent by Weight
7440-66-6	Zinc	99.9 max

State Regulations: The product, **Galvanizing Dross** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

California Prop. 65: NA The product, **Galvanizing Dross** does not contain chemicals which is known to the State of California to cause cancer or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

Other Regulations:

WHMIS Classification (Canadian): The product, **Galvanizing Dross** is not listed as a whole. However individual components are listed.

Ingredients	WHMIS Classification
Silicon	Flammable solids - Category 2 (The classification "Flammable solids" refers to the amorphous form of silicon powder); Combustible dusts**
Iron	Combustible dusts - Category 1 (may form combustible dust concentrations in air)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Prepared By: United States Steel Corporation

Revision History:

Expiration Date: 12/31/2023

- 12/31/2020 – Update to sections 2, 8, 11, 15
- 07/01/2017 – Update WHMIS 2015
- 06/12/2014 - Update to OSHA HAZCOM 2012
- 05/02/2011 – Update of content and format to comply with GHS
- 11/25/1385 - Original

Galvanizing Dross

USS IHS No.: 1824

Rev. 12/20

Section 16 - Other Information (continued)

Additional Information:

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

HEALTH= 1, * Denotes possible chronic hazard if airborne dusts or fumes are generated Irritation or minor reversible injury possible.
 FIRE= 0, Materials that will not burn.
 PHYSICAL HAZARDS = 0, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.
 FIRE = 0, Materials that will not burn.
 INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive with water.

ABBREVIATIONS/ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists	NIF	No Information Found
BEIs	Biological Exposure Indices	NIOSH	National Institute for Occupational Safety and Health
CAS	Chemical Abstracts Service	NTP	National Toxicology Program
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act	ORC	Organization Resources Counselors
CFR	Code of Federal Regulations	OSHA	Occupational Safety and Health Administration
CNS	Central Nervous System	PEL	Permissible Exposure Limit
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract	PNOR	Particulate Not Otherwise Regulated
HMIS	Hazardous Materials Identification System	PNOC	Particulate Not Otherwise Classified
IARC	International Agency for Research on Cancer	PPE	Personal Protective Equipment
LC50	Median Lethal Concentration	ppm	parts per million
LD50	Median Lethal Dose	RCRA	Resource Conservation and Recovery Act
LD_{Lo}	Lowest Dose to have killed animals or humans	RTECS	Registry of Toxic Effects of Chemical Substances
LEL	Lower Explosive Limit	SARA	Superfund Amendment and Reauthorization Act
µg/m³	microgram per cubic meter of air	SCBA	Self-contained Breathing Apparatus
mg/m³	milligram per cubic meter of air	STEL	Short-term Exposure Limit
mppcf	million particles per cubic foot	TLV	Threshold Limit Value
SDS	Safety Data Sheet	TWA	Time-weighted Average
MSHA	Mine Safety and Health Administration	UEL	Upper Explosive Limit
NFPA	National Fire Protection Association		

Disclaimer: This information is taken from sources or based upon data believed to be reliable. However, United States Steel Corporation makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.